

5L PORTABLE

1 - Mounting

Mount vertically, away from combustible materials. If mounting will be semi-permanent please utilize mounting brackets on the top and bottom center of unit for a more secure result. **DO NOT USE HANDLE TO MOUNT.** Make sure the vent at the top of the unit is clear of combustible material or debris for at least 4 feet, as the exhaust coming out will be hot.

2 - Water connections

Water connections are 1/2" NPT. Cold water and hot water are clearly marked on the bottom of unit. Supplied with the unit is a fitting to utilize a garden hose for your incoming water, also supplied is a shower head that can mounted to the water outlet for your convenience. **DO NOT USE WRENCH TO TIGHTEN SHOWER HEAD.** Please use Teflon tape when installing all fittings to prevent leaks. Purge all the air and pressurize water lines and check for leaks. **NEVER USE PVC FOR YOUR WATER OUTLET.**

3 - Gas Connection

Marey has also provided you with a propane gas regulator and hose to ease with your gas installation. Connect regulator to a standard 20 lbs. bottle of propane, connect the other end of the hose to the 3/8 flared fitting. **DO NOT USE TEFLON TAPE ON FLARED FITTING CONNECTION.** Turn on gas at bottle, pressurize gas lines and check for leaks with a soapy liquid.

4 - Batteries

The battery pack is located at the lower right hand side. Two size "D" batteries are required for the heater to operate. Proper polarity is noted on the inner left hand side of the battery pack door.

5 - Operation

Turn your shower head or faucet to the "on" position allowing water flow. You should hear a series of clicks (pulse ignition) then the burner will ignite, if after 5-10 seconds there is no combustion then check troubleshooting in the manual. There should be a clean burning blue flame visible through the viewing window on the front cover of the unit.

